



ZERO TURN MOWERS



ZTR SERIES

Residential & Commercial

Combining top-tier components with world-class manufacturing, KIOTI ZTRs deliver the same quality, reliability and value KIOTI tractors are known for.

Ergonomic Controls

Comfortable Seating

User-friendly Control Panel

48", 54", & 60" Cutting Widths

Large Fuel Capacity

Excellent Cut Quality







HEAVY DUTY RESIDENTIAL

ZXR48
ZXR54
ZXR60

ZXR48 SE
ZXR54 SE
ZXR60 SE



Heavy Duty Chassis

Robust frame with strong tubular steel and welded ROPS to protect operators.



Rear Guard

Steel rear guard to protect major components with convenient integrated tie-downs.



LED Headlights

LED headlights are standard on ZXR SE models and optional on ZXR models to improve visibility in low light conditions.



Operator Platform with Access Panel

The wide platform designed for operator comfort and convenience allows for easy service and cleaning.



Dial-Type Adjustable Deck System

Ergonomically designed and simple to use adjustable deck system allows for precise cutting heights.



Digital Control Panel / Keyless Start

Easy to use push button keyless start and diagnostics panel.



Engines

The KIOTI ZXR Series is equipped with Briggs & Stratton Professional Series™ gasoline engines ranging from 22 – 27 HP. The KIOTI ZXR SE Series is equipped with Kohler Confidant™ engines ranging from 21 – 25 HP.



Adjustable Suspension Seat

1.5" suspension seat is standard on ZXR SE models. The ZXR models can be outfitted with a 1" suspension kit.



Heavy Gauge Fabricated Deck

10-gauge fabricated deck in 48", 54", and 60" sizes with reinforced 7-gauge edge for long lasting durability.



COMMERCIAL GRADE

ZXC48
ZXC54
ZXC60

ZXC48 SE
ZXC54 SE
ZXC60 SE



Integrated High Capacity Fuel Tanks

The large 12.5 gallon twin fuel tanks will keep you mowing with less downtime for refueling.



Rear Guard

Steel rear guard to protect major components with convenient integrated tie-downs.



12 Volt Charging Adapter

Convenient on board charging for phone and other devices on all models.



Operator Platform with Access Panel

The wide platform designed for operator comfort and convenience allows for easy service and cleaning.



Dial-Type Adjustable Deck System

Ergonomically designed and simple to use adjustable deck system allows for precise cutting heights.



Digital Control Panel / Keyless Start

Easy to use push button keyless start and diagnostics panel.



Engines

The KIOTI ZXC Series is equipped with Briggs & Stratton Commercial Series™ gasoline engines ranging from 23 – 27 HP. The KIOTI ZXC SE Series is equipped with Kohler Command PRO® engines ranging from 22.5 – 25 HP.



Premium Adjustable Seat Suspension

1.5" adjustable suspension seat is standard on ZXC models. 3" suspension seat with high back on ZXC SE models.



Heavy Gauge Fabricated Deck

10-gauge fabricated deck in 48", 54" and 60" sizes with reinforced 7-gauge edge for long lasting durability.

SPECIFICATIONS

| MODEL | ZXR48 | ZXR54 | ZXR60 | ZXR48 SE | ZXR54 SE | ZXR60 SE | ZC48 | ZC54 | ZC60 | ZC48 SE | ZC54 SE | ZC60 SE | |
|-------------------------------|--|-----------------------------------|-------------|-----------------------------------|---|-------------|--------------------------------------|---|--------------|---|--------------|--------------|-------------|
| Type | Heavy-Duty Residential | | | Premium Heavy-Duty Residential | | | Commercial | | | Premium Commercial | | | |
| ENGINE | Briggs & Stratton Professional Series™ | | | Kohler Command™ | | | Briggs & Stratton Commercial Series™ | | | Kohler Command PRO® | | | |
| Engine Gross | hp (kW) | 22 (16.40) | 24 (17.89) | 27 (20.13) | 21 (15.65) | 23 (17.15) | 25 (18.64) | 23 (17.15) | 25 (18.64) | 27 (20.13) | 22.5 (16.77) | 23.5 (17.52) | 25 (18.64) |
| Displacement | cu. in. (cc) | 44.18 (724) | 44.18 (724) | 49.42 (810) | 44.24 (725) | 45.58 (747) | 45.58 (747) | 44.18 (724) | 44.18 (724) | 49.42 (810) | 42.35 (694) | 45.58 (747) | 45.58 (747) |
| Choke | | Auto | | | Manual | Auto | | | Manual Lever | | | | |
| Fuel Capacity | US gal. (ℓ) | 7.5 (28.39) (1 Tank on Left Side) | | | Unleaded Gasoline (87 Octane or Higher) | | | 12.5 (47.31) (2 Tanks: Left and Right Side) | | | | | |
| Fuel Requirement | | | | | | | | | | | | | |
| DRIVE TRAIN | | | | | | | | | | | | | |
| Model | Hydrogear ZT2800 | | | Hydrogear ZT3200 | | | Hydrogear ZT3400 | | | | | | |
| Displacement (Pump/Motor) | cc | | | 10/16 | | | 12/16 | | | | | | |
| PTO TYPE | | | | | | | | | | | | | |
| Clutch | t/lb | | | 125 | | | 200 | | | | | | |
| ELECTRICAL | | | | | | | | | | | | | |
| Charging System | amp | | | 16 | | | 15 | | | 16 | | | |
| TIRE SIZE | | | | | | | | | | | | | |
| Front | 13x6-6 | | | 13x6-5-6 | | | 13x6-5-6 | | | 13x6-5-6 | | | |
| Rear | 23x9-5-10 | | | 23x9-5-12 | | | 23x9-5-12 | | | 23x10-5-12 | | | |
| TRAVELING SPEEDS | | | | | | | | | | | | | |
| Forward | mph (km/h) | | | 8 (12.87) | | | 9 (14.48) | | | 10 (16.1) | | | |
| Parking Brake | Internal Integrated in Axle | | | | | | | | | | | | |
| DIMENSIONS | | | | | | | | | | | | | |
| Overall Length | in. (mm) | | | 80.7 (2,049.78) | | | 81.7 (2,075.18) | | | 80.7 (2,049.78) | | | |
| Overall Width (Chute Down) | in. (mm) | | | 60.7 (1,541.78) 67.3 (1,709.42) | | | 60.7 (1,541.78) 67.3 (1,709.42) | | | 60.7 (1,541.78) 67.3 (1,709.42) | | | |
| Overall Height (ROPS Upright) | in. (mm) | | | 70.5 (1,790.7) | | | 71.5 (1,816.1) | | | 72.6 (1,844.04) | | | |
| Wheelbase | in. (mm) | | | 48.5 (1,231.9) | | | 49.5 (1,257.3) | | | 48.5 (1,231.9) | | | |
| Width (Tire to Tire) | in. (mm) | | | 50.3 (1,277.62) | | | 48.5 (1,231.9) | | | 51.3 (1,303.02) | | | |
| Approximate Curb Weight | lb. (kg) | | | 893 (405.05) 910 (412.76) | | | 948 (430.00) 970 (439.98) | | | 988 (448.14) 999 (453.13) | | | |
| MOWER DECK | | | | | | | | | | | | | |
| Mower Deck Type | Fabricated | | | | | | | | | | | | |
| Lift Mechanism | Foot Pedal | | | | | | | | | | | | |
| Deck Steel Thickness | 10-gauge with 7-gauge at edge area | | | | | | | | | | | | |
| Anti-Scalp Ball Rollers | 5 (4 front, 1 rear) | | | 6 (4 front, 2 rear) | | | 8 (4 front, 4 rear) | | | 5 (4 front, 1 rear) | | | |
| Cutting Width of Mower | in. (mm) | | | 48 (1,219.2) 54 (1,371.6) | | | 60 (1,524) 48 (1,219.2) | | | 54 (1,371.6) 60 (1,524) | | | |
| Blades | Notched (Optional Serrated) | | | | | | | | | | | | |
| Cutting Height | in. (mm) | | | 1.5-5 (38.1-127) | | | Side (Inclined Rubber) | | | Dial Type | | | |
| Discharge Chute | | | | | | | | | | | | | |
| Deck Height Adjustment | | | | | | | | | | | | | |
| SEAT | | | | | | | | | | | | | |
| Suspension | 1" Suspension Kit Available | | | Standard (1.5" Suspension) | | | Standard | | | Standard (3" Suspension with High Back) | | | |
| Steering Adjustment | Standard | | | | | | | | | | | | |
| Arm Rest & Seat Belt | Standard | | | | | | | | | | | | |
| STANDARD/OPTIONAL | | | | | | | | | | | | | |
| Foldable ROPS | Optional | | | Standard | | | Standard | | | Optional | | | |
| Head Light | Standard | | | | | | | | | | | | |

* NOTE : Specifications and design are subject to change without notice. Not available for sale in California.



KIOTI Tractor Division
DAEDONG - USA, INC.
6300 KIOTI Drive, Wendell, NC 27591 USA

Toll free 877-60-KIOTI • Fax 919-374-5001
Web www.KIOTI.com



OPTIONAL EQUIPMENT

- Mulching Kit
- Hitch Kit
- Headlamp Kit
- Work Lamp Kit
- Anti-Scalp Roller Kit (5.4" models only)